

ISO 4162 | DIN 6921



Parafuso cabeça sextavada com falsa anilha

Hexagon flange head bolt | Tornillo de cabeza hexagonal con collar biselado | Vis à tête hexagonale à embase | Viti a testa esagonale flangiata

D	M5	M6	M8	M10	M12	M14	M16	M20
P (1)	0.8	1	1.25	1.5	1.75	2	2	2.5
s	8	10	13	15	16	18	21	27
e min	8.71	10.95	14.26	16.5	17.62	19.86	23.15	29.8
dc max	11.8	14.2	18	22.3	26.6	30.5	35	43
k max	5.4	6.6	8.1	9.2	11.5	12.8	14.4	17.1
b < 125	16	18	22	26	30	34	38	46
125 < b ≤200	-	-	28	32	36	40	44	52
b > 200	-	-	-	-	-	-	57	65
L (mm)	peso/ weight/ peso/ poids/ peso - 1000pc/Kg							
10	3.70							
12	3.90	6.50						
16	4.45	7.30	14.00	24.70				
20	4.95	7.85	15.20	27.70	43.20			
25	6.40	8.95	16.70	29.95	46.60			
30	7.20	11.00	21.70	31.60	50.00	66.80		
35	4.95	12.00	23.70	36.00	53.40	72.50	107	
40	8.75	13.30	25.70	42.40	63.00	78.50	114	
45	9.50	14.50	27.50	45.40	71.95	84.50	122	
50	10.30	15.50	29.50	48.50	76.00	90.50	129	219
55		16.50	31.50	51.70	80.50	96.50	137	230
60		17.50	33.50	54.80	85.00	102.00	144	240
65		18.90	35.50	57.80	89.50	108.00	152	270
70		20.00	37.50	60.90	94.00	113.80	159	292
80		22.00	41.50	67.00	103.00	125.50	174	317
90			45.40	73.00	111.90	137.50	190	342
100			49.40	79.00	120.00	149.50	205	366
110			53.35	85.50	129.50	161.00	220	391
120			57.30	91.50	138.50	173.00	235	416
130							250	440
140							265	465
150							280	490

Outras medidas sob consulta | Other measures upon request | Otras medidas solo bajo encargo | Autres mesures sur demande | Altre misure a richiesta
P (1) passo de rosca | thread pitch | paso de rosca | pas filetage | passo del filetto